




Product series: IM

Item number: E1GA-D107





The IM-240AWNE-HC-23 uses refrigerant R290. This natural refrigerant is not only climate-friendly but also boosts the machine, when it comes to performance and production capacity. The exterior is made of stainless steel. The closed water circuit provides maximum protection against any type of contamination during the entire cubing process. All Hoshizaki machines are easy to use, clean, and maintain.

Unique Technology

A dedicated jet of fresh water is injected into each of the closed cells. Excess water leaves the closed cell through a set of outlets. The cell walls block the freezing water's expansion from all sides while reaching down to -30°C during the cubing process.

Thanks to the automatic rinse cycles, impurities such as minerals, are eliminated from the water resulting in the purest ice possible while your machine is protected from calcification and mineral build-up.

Smart Design

Like all Hoshizaki Ice makers, the IM-240AWNE-HC-23 is designed to last and comes with smart design extras such as a magnetic water pump without direct coupling. This element prevents leakage from the water circuit and improves the life expectancy of the machine.

Perfect Fi

Need to amp up your production capacity? The variable setups with modular bins and bases allow the user to mix and match depending on individual requirements and conditions. The dimensions of the IM-240AWNE-HC-23 are $560 \times 700 \times 880$ mm.

Plug&Play

The smart plug-and-play design guarantees an easy and quick set-up.

SPECIFICATIONS

Product title	Cuber, Modular	Net weight (kg)	74
Production capacity (kg/24h) approx.	170	Gross weight packed (kg)	86
арргох.		Corresponding bin(s)	B140SA, B210SA, B340SA
Electric connection	1/220 - 240V/50Hz		
Electric consumption (kW)	0.8	Icemaking Water Consumption (m³/24h) approx. (AT 10°C, WT 10°C)	0.42
Outside dimensions W x D x H (mm)	560 x 700 x 880	Icemaking Water Consumption (m³/24h) approx. (AT 21°C, WT 15°C)	0.38
Ice type	Medium cubes - 23 (28 x 28 x 23mm)		
Refrigerant	R290	Icemaking Water Consumption (m³/24h) approx. (AT 32°C, WT 21°C)	0.35
CO2 equivalent (kg)	0.000441	Condenser cooling water flow (m³/24h) approx. (AT 10°C, WT 10°C)	0.85
Cooling system	Water Cooled	approx. (A1 10 C, W1 10 C)	
Product configuration	Modular	Condenser cooling water flow (m³/24h) approx. (AT 21°C, WT 15°C)	1.07
		Condenser cooling water flow (m³/24h) approx. (AT 32°C, WT 21°C)	1.42

